

PENWELD S



To the product

Technical data

Voltage	120 V; 230 V	
Frequency	50/60 Hz	
Power	1000-1550 W	
Temperature	60-600 °C	140.0-1112.0 °F
Temperature setting stepless	Yes	
Display	No	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in; M14	
Length	254.0-275.0 mm	10.0-10.82 in
Device diameter	54 mm	2.12 in
Handle diameter	37 mm	1.45 in
Weight	0.41-0.46 kg	0.9-1.01 lb
Power cable length	0.5 m	1.64 ft
Approvals	CE; UKCA	
Protection class	II	
Country of origin	CH	



PENWELD S

Product items

173.372	PENWELD 305-S, 230V/1000W, 3m, M14, EU plug
173.373	PENWELD 305-S, 230V/1000W, 3m, M14, CH plug
173.374	PENWELD 305-S, 120V/1000W, 3m, M14, US plug
173.375	PENWELD 305-S, 230V/1000W, 8m, M14, EU plug
173.378	PENWELD 500-S, 230V/1550W, 3m, EU plug
173.379	PENWELD 500-S, 120V/1550W, 3m, US plug
177.345	PENWELD 500-S, 230V/1550W, 3m, CN plug